NSN 5935-00-961-3995

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-961-3995

| Thread Class: |
|--|
| 2a and 2b |
| Thread Direction: |
| Right-hand |
| Overall Length: |
| 1.060 inches |
| Overall Height: |
| 0.500 inches |
| Overall Width: |
| 0.270 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 20 20-20 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Thread Size: |
| 0.086 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-19833, type gdi-30 military specification single material response single mating end |
| Included Contact Quantity: |
| 20 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |

NSN 5935-00-961-3995

Electrical Plug Connector - Page 2 of 2



| Precious Material And Weight: |
|-------------------------------|
| 0.020 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-m-19833 spec.