NSN 5935-00-961-5499

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-961-5499

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

2.312 inches

Overall Height:

Between 1.729 inches and 1.781 inches

Overall Width:

Between 1.729 inches and 1.781 inches

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.152 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.270 inches and 1.280 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.370 inches and 1.380 inches

Distance From Mounting Shoulder To Front Face:

Between 0.812 inches and 0.842 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

24-22 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

73.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Split

Connector Locking Method:

Externally threaded shell

NSN 5935-00-961-5499

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.437 inches and 1.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize and dichromate
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0