Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-964-3304

Body Style:
Straight shape, external coupling
Overall Length:
1.125 inches
Overall Height:
Between 1.433 inches and 1.443 inches
Overall Width:
Between 1.433 inches and 1.443 inches
Environmental Protection:
Pressure proof
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.182 inches and 1.192 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.182 inches and 1.192 inches
Distance From Mounting Shoulder To Front Face:
Between 0.526 inches and 0.536 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3719p single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Ball
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Insert Material:
Rubber single mating end



Terminal Type: Solder well single mating end all contact groupings Shell Material: Aluminum **Shell Surface Treatment:** Cadmium Shell Surface Treatment Specification: Qq-p-416, cl 2, type ii federal specification single treatment response **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Included Contact Type:** Round pin single mating end 1st contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.019 gold grains, troy and 0.019 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig:

A039b0