Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-964-4119

Thread	Class
Inread	Class:

2a

**Thread Direction:** 

Right-hand

# Body Style:

Straight shape

## **Overall Length:**

2.110 inches

## **Overall Height:**

0.700 inches

## **Overall Width:**

0.360 inches

# Distance Between Mounting Facility Centers:

1.810 inches

## **Threaded Device Type:**

# Mounting stud

# Mating End Quantity:

1

## **Contact Position Arrangement Style:**

15 single mating end

# **Contact Removability:**

Nonremovable single mating end single contact grouping

# **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

#### Thread Size:

0.112 inches

# **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Solder well single mating end single contact grouping

# **Contact Material Specification:**

Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping

# **Insert Material Specification:**

Mil-p-19833, ty gdi-30f military specification single material response single mating end

# NSN 5935-00-964-4119

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 15 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-p-19833 spec.