

View Online at <https://aerobasegroup.com/nsn/5935-00-965-6964>

**Body Style:**

Straight shape, external coupling w/strain relief

**Overall Length:**

2.062 inches

**Overall Diameter:**

1.062 inches

**Cable Entrance Diameter:**

0.312 inches

**Distance From Mounting Shoulder To Front Face:**

0.656 inches

**Mounting Facility Thickness:**

0.094 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

12-p single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Ball

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Special Features:**

Solder flange mount

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.012 gold grains, troy and 0.012 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0