

View Online at <https://aerobasegroup.com/nsn/5935-00-965-9702>

Body Style:

Straight shape

Overall Length:

3.600 inches

Overall Height:

0.828 inches

Overall Width:

0.531 inches

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

3.334 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-b-750, comp a military specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14f, type sdg-f military specification single material response single mating end

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

spec.