## NSN 5935-00-965-9702

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-965-9702

Body Style:
Straight shape
Overall Length:
3.600 inches
Overall Height:
0.828 inches
Overall Width:
0.531 inches
Unthreaded Mounting Hole Diameter:
0.128 inches
Distance Between Mounting Facility Centers:
3.334 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
10.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a military specification single material response single mating end single contact grouping
Insert Material Specification:

Mil-m-14f, type sdg-f military specification single material response single mating end

## NSN 5935-00-965-9702

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
29 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.029 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

spec.

Mil-std (military Standard):