## NSN 5935-00-966-1936

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-966-1936

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, flush mount
Overall Length:
1.593 inches
Overall Height:
1.000 inches
Overall Width:
0.729 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.593 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Thready Qty Per Inch (tpi):
48
Thread Size:
0.099 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military
specification 2nd treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Contact Material Specification:

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Qq-b-746, comp a federal specification single material response single mating end single contact grouping

## NSN 5935-00-966-1936

Electrical Receptacle Connector - Page 2 of 2



## **Included Contact Quantity:** 9 single mating end single contact grouping

**Included Contact Type:** 

Spring pincers single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.009 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.