## NSN 5935-00-967-9581

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-967-9581 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.156 inches **Overall Diameter:** Between 1.485 inches and 1.515 inches **Distance From Mounting Shoulder To Front Face:** Between 0.641 inches and 0.671 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 3719p single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 1st contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid Radio Frequency Type Contact Characteristic Impedance In Ohms: 90.0 single mating end 2nd contact grouping Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.250 inches **Terminal Location:** Back single mating end all contact groupings **Insert Material:** Plastic single mating end **Shell Material:** 

Aluminum alloy

## NSN 5935-00-967-9581

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
6 single mating end 2nd contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round socket single mating end 1st contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0