

View Online at <https://aerobasegroup.com/nsn/5935-00-968-0370>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/flange

Overall Length:

2.094 inches

Overall Height:

2.500 inches

Overall Width:

2.500 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

0.173 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.938 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.938 inches

Distance From Mounting Shoulder To Front Face:

0.750 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

36-52 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Current Rating In Amps:

22.0 all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

700.0 all mating ends all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.685 inches

Thread Qty Per Inch (tpi):

16

Thread Size:

2.250 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Silver all mating ends all contact groupings

Insert Material:

Rubber all mating ends

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

52 1st mating end all contact groupings

Included Contact Type:

Round socket 2nd mating end all contact groupings

Special Features:

Polarizing position x

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.104 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0