NSN 5935-00-968-4299

Thread Class: 2a and 2b

Body Style:

Overall Length: 2.050 inches Overall Height: 2.075 inches Overall Width:

Thread Direction:

Right-hand and right-hand

Hood, side opening w/clamp

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-968-4299

| 0.570 inches |
|---|
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Cable Entrance Diameter: |
| Between 0.310 inches and 0.590 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 34 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, side opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 0.086 inches and 0.086 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| |
| |
| |

NSN 5935-00-968-4299

Electrical Plug Connector - Page 2 of 2



| Insert Material: |
|---|
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-p-330 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Shell Surface Treatment Specification: |
| Mil-a-8625, type 2 military specification single treatment response |
| Insert Material Specification: |
| Mil-m-19833, type gdi-30 military specification single material response single mating end |
| Included Contact Quantity: |
| 34 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.034 gold grains, troy and 0.034 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-m-19833 spec. |
| |