

View Online at <https://aerobasegroup.com/nsn/5935-00-968-4326>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Overall Length:

1.266 inches

Temperature Rating:

-45.0 degrees fahrenheit and 145.0 degrees fahrenheit

Overall Height:

0.594 inches

Overall Width:

0.391 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Body Mounting Hole Accommodation Length:

Between 0.778 inches and 0.786 inches

Body Mounting Hole Accommodation Width:

Between 0.401 inches and 0.411 inches

Mounting Hole Style:

Rectangular, w/two mounting holes/slots

Specific Equipment Accommodated:

Relay

Contact Maximum Current Rating In Amps:

5.0

Contact Material:

Phosphor bronze

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

8

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.990 inches and 1.010 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.120 inches and 0.130 inches

Component Shield Mounting Method:

Force fit

Polarization Type:

Off center hole

Projection Length Below Mounting Surface:

Between 0.234 inches and 0.266 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

Symmetrical

Contact Maximum Voltage In Volts And Current Type:

1000.0 ac and 1000.0 dc

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Furnished Items And Quantity:

2 screw and 2 lock washer and 2 flat washer and 2 nut

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02300