

View Online at <https://aerobasegroup.com/nsn/5935-00-968-4326>

**Body Material:**

Plastic

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Top mount w/studs

**Overall Length:**

1.266 inches

**Temperature Rating:**

-45.0 degrees fahrenheit and 145.0 degrees fahrenheit

**Overall Height:**

0.594 inches

**Overall Width:**

0.391 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Body Mounting Hole Accommodation Length:**

Between 0.778 inches and 0.786 inches

**Body Mounting Hole Accommodation Width:**

Between 0.401 inches and 0.411 inches

**Mounting Hole Style:**

Rectangular, w/two mounting holes/slots

**Specific Equipment Accommodated:**

Relay

**Contact Maximum Current Rating In Amps:**

5.0

**Contact Material:**

Phosphor bronze

**Contact Surface Treatment:**

Gold and silver

**Accommodated Contact Quantity:**

8

**Center To Center Distance Between Outside Mounting Holes Along Length:**

Between 0.990 inches and 1.010 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

Between 0.120 inches and 0.130 inches

**Component Shield Mounting Method:**

Force fit

**Polarization Type:**

Off center hole

**Projection Length Below Mounting Surface:**

Between 0.234 inches and 0.266 inches

**Mounting Method:**

Threaded stud

**Mounting Type For Which Designed:**

Chassis

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Contact Position Arrangement Style:**

Symmetrical

**Contact Maximum Voltage In Volts And Current Type:**

1000.0 ac and 1000.0 dc

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.008 gold grains, troy and 0.008 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unc

**Furnished Items And Quantity:**

2 screw and 2 lock washer and 2 flat washer and 2 nut

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300