NSN 5935-00-968-5015

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-968-5015 |
|--|
| Thread Class: |
| 2g |
| Thread Pitch Diameters: |
| +1.989/+2.000 inches |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling w/backshell |
| Overall Length: |
| 2.328 inches |
| Overall Height: |
| 2.250 inches |
| Overall Width: |
| 2.250 inches |
| Environmental Protection: |
| Pressure proof and salt water resistant and vibration resistant and watertight |
| Unthreaded Mounting Hole Diameter: |
| 0.203 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.687 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.687 inches |
| Distance From Mounting Shoulder To Front Face: |
| 1.000 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 16-11 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 41.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| |

0.0

NSN 5935-00-968-5015

Electrical Receptacle Connector - Page 2 of 2



| Shell Type: |
|--|
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Thread Length: |
| 1.000 inches |
| Thready Qty Per Inch (tpi): |
| 4 |
| Thread Size: |
| 2.000 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Rubber synthetic single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 19 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.019 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Special acme |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A039b0