NSN 5935-00-968-5015

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-968-5015
Thread Class:
2g
Thread Pitch Diameters:
+1.989/+2.000 inches
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
2.328 inches
Overall Height:
2.250 inches
Overall Width:
2.250 inches
Environmental Protection:
Pressure proof and salt water resistant and vibration resistant and watertight
Unthreaded Mounting Hole Diameter:
0.203 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.687 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.687 inches
Distance From Mounting Shoulder To Front Face:
1.000 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
16-11 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
41.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway

0.0

NSN 5935-00-968-5015

Electrical Receptacle Connector - Page 2 of 2



Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
1.000 inches
Thready Qty Per Inch (tpi):
4
Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber synthetic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Included Contact Quantity:
19 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.019 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Special acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0