## NSN 5935-00-968-5434

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-968-5434

view Offline at https://aerobasegroup.com/nsi//3335-00-300-3454
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
1.187 inches
Overall Height:
1.208 inches
Overall Width:
1.203 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.901 inches and 0.911 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.901 inches and 0.911 inches
Distance From Mounting Shoulder To Front Face:
0.542 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
194p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Detent
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:

Onen material

Aluminum alloy

NSN 5935-00-968-5434 Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A039b0