

View Online at <https://aerobasegroup.com/nsn/5935-00-968-7651>

Body Material:

Plastic

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Top mount w/studs

Fabrication Method:

Molded

Overall Length:

1.725 inches

Tempurature Rating:

-40.0 degrees fahrenheit and 145.0 degrees fahrenheit

Overall Height:

0.828 inches

Overall Width:

0.525 inches

Mounting Hole Diameter:

Between 0.133 inches and 0.143 inches

Distance Between Mounting Facility Centers:

Between 1.140 inches and 1.411 inches

Mounting Hole Style:

Two mounting holes/slots, in-line

Specific Equipment Accommodated:

Socket relay

Contact Maximum Current Rating In Amps:

5.0

Contact Material:

Phosphor bronze

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

8

Projection Length Below Mounting Surface:

Between 0.258 inches and 0.268 inches

Mounting Method:

Threaded stud

Mounting Type For Which Designed:

Chassis

Thready Qty Per Inch (tpi):

32

Thread Size:

0.138 inches

Contact Position Arrangement Style:

Dual in line

Contact Maximum Voltage In Volts And Current Type:

3500.0 ac and 3500.0 dc

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Furnished Items And Quantity:

2 lock washer and 2 nut

Terminal Type And Quantity:

8 solder well

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300