

View Online at <https://aerobasegroup.com/nsn/5935-00-969-5601>

Body Style:

Angle, shape, internal coupling

Overall Length:

0.734 inches

Environmental Protection:

Salt water resistant

Cable Entrance Diameter:

0.195 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Crimp type

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Operating Temperature Rating:

Between -65.0 degrees celsius and 150.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Salt spray resistant

Precious Material And Location:

Contact and body surfaces gold

Precious Material And Weight:

0.101 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0