## NSN 5935-00-969-7166

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-	969-7166
Body Style:	
Straight shape	
Overall Length:	
2.880 inches	
Overall Height:	
0.739 inches	
Overall Width:	
1.065 inches	
Unthreaded Mounting Hole Diameter:	
0.120 inches	
Distance Between Mounting Facility Centers:	
2.531 inches	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
50 single mating end	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
1.5 single mating end single contact grouping	
Contact Maximum Ac Voltage Rating In Volts:	
600.0 single mating end single contact grouping	
Contact Maximum Dc Voltage Rating In Volts:	
750.0 single mating end single contact grouping	
Polarization Method:	
Mating end	
Shell Type:	
Solid	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Insert Material:	
Plastic diallyl phthalate single mating end	

**Insert Material Specification:** 

**Terminal Type:** 

Mil-m-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:** 

50 single mating end single contact grouping

Crimp single mating end single contact grouping

## NSN 5935-00-969-7166

Electrical Receptacle Connector - Page 2 of 2



## Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold Precious Material And Weight: 0.050 gold grains, troy Precious Material: Gold Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.