NSN 5935-00-969-9337

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-969-9337 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Bottom mount w/metal saddle **Fabrication Method:** Molded **Overall Length:** 1.795 inches Tempurature Rating: -65.0 degrees celsius and 125.0 degrees celsius **Overall Height:** 2.218 inches **Overall Width:** 1.077 inches **Mounting Hole Diameter:** Between 0.133 inches and 0.143 inches **Body Mounting Hole Accommodation Diameter:** 0.983 inches **Distance Between Mounting Facility Centers:** Between 1.396 inches and 1.416 inches **Mounting Hole Style:** Round, w/two mounting holes **Specific Equipment Accommodated:** Socket relay **Contact Maximum Current Rating In Amps:** 7.5 **Contact Material:** Phosphor bronze **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity:** 20 **Missing Contact Designation:** 10th contact position **Polarization Type:** Contact position **Projection Length Above Mounting Surface:**

1.700 inches

NSN 5935-00-969-9337

Plug-in Electronic Components Socket - Page 2 of 2



| Mounting Method: |
|---|
| Threaded stud |
| Mounting Type For Which Designed: |
| Chassis |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Contact Maximum Voltage In Volts And Current Type: |
| 1500.0 ac and 1500.0 dc |
| Precious Material And Location: |
| Contact surfaces gold and contact surfaces silver |
| Precious Material And Weight: |
| 0.020 gold grains, troy and 0.020 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Thread Series Designator: |
| Unc |
| Furnished Items And Quantity: |
| 2 nut and 2 screw and 2 spacer |
| Terminal Type And Quantity: |
| 20 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A02300 |