

View Online at <https://aerobasegroup.com/nsn/5935-00-971-2241>

**Body Style:**

Straight shape, flush mount

**Overall Length:**

1.109 inches

**Overall Height:**

1.688 inches

**Overall Width:**

3.375 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and shock resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.875 inches

**Distance From Mounting Shoulder To Front Face:**

0.062 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

90 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Polarization Method:**

1 polarization post

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification single treatment response

**Included Contact Quantity:**

90 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.090 gold grains, troy and 0.090 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0