

View Online at <https://aerobasegroup.com/nsn/5935-00-971-2241>

Body Style:

Straight shape, flush mount

Overall Length:

1.109 inches

Overall Height:

1.688 inches

Overall Width:

3.375 inches

Environmental Protection:

Moisture resistant and salt water resistant and shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.000 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.875 inches

Distance From Mounting Shoulder To Front Face:

0.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

90 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

10.0 single mating end single contact grouping

Polarization Method:

1 polarization post

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Included Contact Quantity:

90 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.090 gold grains, troy and 0.090 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0