NSN 5935-00-971-2243

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-971-2243

Straight shape, flush mount
Overall Length:
1.227 inches
Overall Height:
1.688 inches
Overall Width:
3.375 inches
Environmental Protection:
Moisture resistant and shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.144 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.875 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
112 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end single contact grouping
Polarization Method:
Contact
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum

NSN 5935-00-971-2243

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Included Contact Quantity:
112 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.112 gold grains, troy and 0.112 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0