## NSN 5935-00-973-8147

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-973-8147

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling w/backshell
Overall Length:
1.279 inches
Overall Diameter:
Between 0.865 inches and 0.885 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
12s-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Size:
0.625 inches and 0.750 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

## **NSN 5935-00-973-8147** Electrical Plug Connector - Page 2 of 2



ubber single mating end	
erminal Type:	
older well single mating end single contact grouping	
hell Material:	
luminum alloy	
hell Surface Treatment:	
admium	
hell Surface Treatment Specification:	
q-p-416, type 2, cl 3 federal specification single treatment	t response
cluded Contact Quantity:	
single mating end single contact grouping	
cluded Contact Type:	
ound socket single mating end single contact grouping	
recious Material And Location:	
ontact surface gold	
recious Material And Weight:	
002 gold grains, troy	
recious Material:	
old	
hread Series Designator:	
nef and unef	
helf Life:	
/a	
nit Of Measure:	
emilitarization:	
0	
iig:	
039b0	