

View Online at <https://aerobasegroup.com/nsn/5935-00-974-5684>

Body Style:

Straight shape w/flange

Overall Length:

2.250 inches

Overall Height:

1.566 inches

Overall Width:

1.566 inches

Unthreaded Mounting Hole Diameter:

Between 0.119 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.281 inches

Distance From Mounting Shoulder To Front Face:

Between 0.750 inches and 0.781 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

22-55 all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Insert Material:

Rubber all mating ends

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625 military specification single treatment response

Included Contact Quantity:

55 all mating ends single contact grouping

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.110 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.