Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-974-6088

| view Online at https://aerobasegroup.com/nsn/3953-00-974-0000 |
|---|
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 1.191 inches |
| Overall Diameter: |
| 0.500 inches |
| Threaded Device Type: |
| Back shell |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Bnc single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Bayonet pin |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.375 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic polytetrafluoroethylene single mating end |
| Contact Surface Treatment Specification: |
| Bmil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| |

NSN 5935-00-974-6088

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment: Nickel Included Contact Quantity: 1 single mating end single contact grouping Included Contact Type: Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.