NSN 5935-00-974-6553

Thread Class: 2a and 2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-974-6553

| Thread Direction: |
|---|
| Right-hand |
| Body Style: |
| Hood, top opening w/clamp |
| Overall Length: |
| 1.630 inches |
| Overall Height: |
| 2.610 inches |
| Overall Width: |
| 0.560 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 7.5 single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize or passivate |
| Insert Material Specification: |
| Mil-m-19833 ty gdi-30 military specification single material response single mating end |
| Included Contact Quantity: |
| 26 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |

NSN 5935-00-974-6553

Electrical Plug Connector - Page 2 of 2



| Thread Series Designator: |
|------------------------------|
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |

Mil-m-19833 spec.