## NSN 5935-00-974-6873

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-974-6873

**Body Style:** Straight shape **Overall Length:** Between 1.526 inches and 1.556 inches **Overall Height:** 0.663 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Unthreaded Mounting Hole Diameter:** Between 0.086 inches and 0.091 inches **Distance Between Mounting Facility Centers:** Between 1.307 inches and 1.317 inches **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:** Cadmium and chromate

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification all treatment responses

**Insert Material Specification:** 

Mil-p-19833, type gdi-30f military specification single material response single mating end

# NSN 5935-00-974-6873

Electrical Receptacle Connector - Page 2 of 2



### **Included Contact Quantity:**

5 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.005 gold grains, troy and 0.005 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.