NSN 5935-00-975-4446

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-975-4446

Body Style:

Straight edge type w/mounting flange

Overall Length:

4.342 inches

Overall Height:

1.422 inches

Overall Width:

0.390 inches

Environmental Protection:

Shock resistant and salt water resistant and moisture proof and vibration proof

Unthreaded Mounting Hole Diameter:

0.128 inches

Distance Between Mounting Facility Centers:

4.030 inches

Board Accommodated Length:

3.596 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c533 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification all material responses single mating end or mil-p-19833, ty gdi-30 military specification all material responses single mating end

NSN 5935-00-975-4446

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 44 single mating end single contact grouping **Included Contact Type:** Bifurcated spring single mating end single contact grouping Color: Natural **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.044 gold grains, troy **Precious Material:** Gold Fsc Application Data (non-core): Connectors, electrical Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.