## NSN 5935-00-975-6935

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-975-6935 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.719 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.282 inches **Overall Height:** 0.375 inches **Overall Width:** 1.234 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.756 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 75 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction Thread Length: 0.266 inches **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Gold single mating end single contact grouping

**Contact Surface Treatment:** 

## NSN 5935-00-975-6935

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate mineral filled single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
75 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.075 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Mo

Fiig: A039b0