## NSN 5935-00-976-4872

14 single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



 $\label{thm:com/nsn/5935-00-976-4872} View \ Online \ at \ https://aerobasegroup.com/nsn/5935-00-976-4872$ 

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.250 inches
Overall Height:
0.875 inches
Overall Width:
0.438 inches
Distance Between Mounting Facility Centers:
0.937 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
14 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic polytetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:

## NSN 5935-00-976-4872

Electrical Receptacle Connector - Page 2 of 2



I	n	cl	ud	ed	I C	on	ıta	ct	Tν	ne	

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.014 gold grains, troy and 0.014 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0