Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-978-3931



#### Thread Class:

2a and 2b

**Thread Direction:** 

Right-hand

#### Body Style:

Hood, top opening w/clamp

#### **Overall Length:**

1.219 inches

#### **Overall Height:**

1.687 inches

**Overall Width:** 

0.438 inches

#### Cable Entrance Diameter:

0.312 inches

#### **Threaded Device Type:**

#### Coupling facility

Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

7 single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

## Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

#### Contact Maximum Dc Voltage Rating In Volts:

300.0 single mating end single contact grouping

#### **Polarization Method:**

Jackscrew

#### Shell Type:

Hood, top opening

#### **Connector Locking Method:**

Jackscrew-socket

#### Connector Cable Strain Relief Method:

Cable clamp

#### Thread Length:

0.266 inches

#### Thready Qty Per Inch (tpi):

40

# Thread Size:

0.112 inches

### **Terminal Location:**

Back single mating end single contact grouping

# NSN 5935-00-978-3931

Electrical Plug Connector - Page 2 of 2



**Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic melamine mineral filled single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Anodize **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.007 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0