

View Online at <https://aerobasegroup.com/nsn/5935-00-978-4573>

Body Style:

Straight shape, internal coupling

Overall Length:

Between 0.641 inches and 0.672 inches

Overall Diameter:

Between 0.359 inches and 0.391 inches

Environmental Protection:

Moisture resistant and salt water resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Axial hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.105 silver grains, troy

Precious Material:

Silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0