NSN 5935-00-978-4895

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-978-4895

Thread Direction: Right-hand Body Style: Straight shape w/strain relief Overall Length: 10.250 inches Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Minimum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type: Screw single mating end single contact grouping	The state of
Thread Direction: Right-hand Body Style: Straight shape w/strain relief Overall Length: 10.250 inches Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Thread Class:
Right-hand Body Style: Straight shape w/strain relief Overall Length: 10.250 inches Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping	
Body Style: Straight shape w/strain relief Overall Length: 10.250 inches Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Straight shape w/strain relief Overall Length: 10.250 inches Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Overall Length: 10.250 inches Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Overall Diameter: 4.125 inches Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	•
Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Environmental Protection: Waterproof Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Cable Entrance Diameter: 1.875 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	·
Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	••
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Mating End Quantity:
Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	·
Contact Maximum Current Rating In Amps: 100.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Contact Removability:
Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts: 600.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Contact Maximum Current Rating In Amps:
Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	100.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Contact Maximum Ac Voltage Rating In Volts:
Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	600.0 single mating end single contact grouping
Polarization Method: Key, multiple key groove Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Contact Maximum Dc Voltage Rating In Volts:
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	250.0 single mating end single contact grouping
Insert Position In Deg: 0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Polarization Method:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Key, multiple key groove
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Insert Position In Deg:
Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	0.0
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Shell Type:
Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Solid
Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Connector Locking Method:
Cable clamp Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Internally threaded coupling ring
Terminal Location: Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Connector Cable Strain Relief Method:
Back single mating end single contact grouping Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Cable clamp
Contact Surface Treatment: Silver single mating end single contact grouping Terminal Type:	Terminal Location:
Silver single mating end single contact grouping Terminal Type:	Back single mating end single contact grouping
Terminal Type:	Contact Surface Treatment:
	Silver single mating end single contact grouping
Screw single mating end single contact grouping	Terminal Type:
	Screw single mating end single contact grouping

NSN 5935-00-978-4895

Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.015 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0