

View Online at <https://aerobasegroup.com/nsn/5935-00-978-4897>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape w/strain relief

Overall Length:

10.250 inches

Overall Diameter:

2.812 inches

Environmental Protection:

Waterproof

Cable Entrance Diameter:

1.312 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

3 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

100.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Cable clamp

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Terminal Type:

Screw w/wire lock single mating end single contact grouping

Shell Material:

Aluminum

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.015 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Npt

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0