Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-978-6731

### Overall Length:

2.062 inches

### **Overall Diameter:**

Between 0.657 inches and 0.719 inches

# Cable Entrance Diameter:

0.222 inches

### **Mounting Facility Thickness:**

0.127 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Bnc single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

### Contact Maximum Frequency Rating:

10000.0 megahertz single mating end single contact grouping

### Shell Type:

Solid

## Connector Locking Method:

Bayonet pin

## **Connector Cable Strain Relief Method:**

Crimp type

## Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

#### **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic tetrafluoroethylene single mating end

#### **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Copper alloy

#### **Included Contact Quantity:**

1 single mating end single contact grouping

### **Bushing Accommodation Hole Shape:**

Round w/flat



Included Contact Type:

Coaxial socket single mating end single contact grouping

**Special Features:** 

Gasket

**Precious Material And Location:** 

Contact surface gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0