

View Online at <https://aerobasegroup.com/nsn/5935-00-980-0434>

**Body Material:**

Plastic

**Body Style:**

Top mount w/molded saddle

**Fabrication Method:**

Molded

**Overall Length:**

2.218 inches

**Temperature Rating:**

-65.0 degrees celsius and 120.0 degrees celsius

**Overall Height:**

0.659 inches

**Overall Width:**

1.062 inches

**Mounting Hole Diameter:**

Between 0.191 inches and 0.201 inches

**Body Mounting Hole Accommodation Diameter:**

Between 1.834 inches and 1.854 inches

**Distance Between Mounting Facility Centers:**

Between 1.839 inches and 1.849 inches

**Mounting Hole Style:**

Round, w/two mounting holes

**Specific Equipment Accommodated:**

Electron tube

**Contact Maximum Current Rating In Amps:**

10.0

**Contact Material:**

Copper alloy

**Contact Surface Treatment:**

Gold and silver

**Accommodated Contact Quantity:**

8

**Polarization Type:**

Off center hole

**Projection Length Above Mounting Surface:**

Between 0.083 inches and 0.103 inches

**Mounting Method:**

Saddle

**Mounting Type For Which Designed:**

Chassis

**Contact Position Arrangement Style:**

Triple in line

**Contact Maximum Voltage In Volts And Current Type:**

2500.0 ac and 2500.0 dc

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.008 gold grains, troy and 0.008 silver grains, troy

**Precious Material:**

Gold and silver

**Test Data Document:**

96906-ms25324 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

8 tab, solder lug

**Specification Data:**

96906-ms26324 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02300