

View Online at <https://aerobasegroup.com/nsn/5935-00-980-0434>

Body Material:

Plastic

Body Style:

Top mount w/molded saddle

Fabrication Method:

Molded

Overall Length:

2.218 inches

Temperature Rating:

-65.0 degrees celsius and 120.0 degrees celsius

Overall Height:

0.659 inches

Overall Width:

1.062 inches

Mounting Hole Diameter:

Between 0.191 inches and 0.201 inches

Body Mounting Hole Accommodation Diameter:

Between 1.834 inches and 1.854 inches

Distance Between Mounting Facility Centers:

Between 1.839 inches and 1.849 inches

Mounting Hole Style:

Round, w/two mounting holes

Specific Equipment Accommodated:

Electron tube

Contact Maximum Current Rating In Amps:

10.0

Contact Material:

Copper alloy

Contact Surface Treatment:

Gold and silver

Accommodated Contact Quantity:

8

Polarization Type:

Off center hole

Projection Length Above Mounting Surface:

Between 0.083 inches and 0.103 inches

Mounting Method:

Saddle

Mounting Type For Which Designed:

Chassis

Contact Position Arrangement Style:

Triple in line

Contact Maximum Voltage In Volts And Current Type:

2500.0 ac and 2500.0 dc

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

96906-ms25324 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

96906-ms26324 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A02300