NSN 5935-00-982-0298

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-982-0298

| Body Style: |
|---|
| Straight shape |
| Overall Length: |
| 3.695 inches |
| Overall Height: |
| 0.676 inches |
| Overall Width: |
| 0.340 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.128 inches |
| Distance Between Mounting Facility Centers: |
| 3.406 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 1 row of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end single contact grouping |
| Polarization Method: |
| Contact to contact polarizing keys |
| Terminal Location: |
| Side single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Tab, solder lug single mating end single contact grouping |
| Insert Material Specification: |
| Mil-m-14, type mdg military specification single material response single mating end |
| Included Contact Quantity: |

18 single mating end single contact grouping Included Contact Type:

Flat pin single mating end single contact grouping

Special Features:

Polarized at contact position u

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

NSN 5935-00-982-0298

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Weight: |
|---|
| 0.018 gold grains, troy and 0.018 silver grains, troy |
| Precious Material: |
| Gold and silver |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-m-14 spec.