## NSN 5935-00-982-6312

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-982-6312

**Body Style:** Straight shape **Overall Length:** Between 2.714 inches and 2.744 inches **Overall Height:** 0.660 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and thermal shock resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 2.495 inches and 2.505 inches **Mating End Quantity: Contact Position Arrangement Style:** 21 single mating end **Contact Removability:** Nonremovable single mating end 2nd contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 425.0 single mating end 2nd contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end 2nd contact grouping **Contact Material:** Copper alloy single mating end 2nd contact grouping **Contact Surface Treatment:** 

Insert Material:

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Gold single mating end 2nd contact grouping

Mil-g-45204 military specification single treatment response single mating end 2nd contact grouping

**Terminal Type:** 

Solder well single mating end 2nd contact grouping

## NSN 5935-00-982-6312

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:
Qq-b-626a, comp 22 federal specification single material response single mating end 2nd contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416a, type 2, cl 2 federal specification all treatment responses
Shell Material Specification:
Qq-s-636 federal specification single material response
Insert Material Specification:
Mil-m-14, ty sdg military specification single material response single mating end
Included Contact Quantity:
17 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.017 gold grains, troy and 0.017 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.