

View Online at <https://aerobasegroup.com/nsn/5935-00-982-9711>

**Environmental Protection:**

Watertight

**Mating End Quantity:**

1

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

15.0 single mating end all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end all contact groupings

**Polarization Method:**

Contact

**Terminal Location:**

Side single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Screw single mating end all contact groupings

**Included Contact Quantity:**

2 single mating end 1st contact grouping

**Included Contact Type:**

U-socket single mating end 2nd contact grouping

**Special Features:**

W/std rectangular metal wall plate

**Test Data Document:**

81349-w-c-596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-w-c-596 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0