

View Online at <https://aerobasegroup.com/nsn/5935-00-983-5415>

Body Style:

Straight edge type

Overall Length:

4.344 inches

Overall Height:

0.375 inches

Overall Width:

0.779 inches

Unthreaded Mounting Hole Diameter:

0.116 inches

Distance Between Mounting Facility Centers:

4.030 inches

Board Accommodated Length:

3.596 inches single board

Board Accommodated Width:

0.062 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

1 row of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

800.0 single mating end single contact grouping

Polarization Method:

Contact to contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

28 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Special Features:

Polarizing key located position m

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.028 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.