## NSN 5935-00-983-5426

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-983-5426

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

4.344 inches

**Overall Height:** 

0.375 inches

**Overall Width:** 

0.779 inches

**Unthreaded Mounting Hole Diameter:** 

0.116 inches

**Distance Between Mounting Facility Centers:** 

4.030 inches

**Board Accommodated Length:** 

3.596 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.071 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:** 

800.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

**Criticality Code Justification:** 

Feat

**Terminal Type:** 

Solder well single mating end single contact grouping

## NSN 5935-00-983-5426

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:** 

56 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated accordian leaf spring single mating end single contact grouping

**Special Features:** 

Polarizing key located position x

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.056 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.