Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-983-5491

Thread	Class:
mouu	01400.

2a and 2b

Thread Direction:

Right-hand

Body Style:

Hood, top opening w/clamp

Overall Length:

0.870 inches

Overall Height:

0.895 inches

Overall Width:

0.330 inches

Environmental Protection:

Vibration resistant and heat resistant and cold resistant and salt water resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

14 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Shell Type:

Hood, top opening

Connector Locking Method:

Jackscrew-socket

Connector Cable Strain Relief Method:

Cable clamp

Cable Opening Length:

0.360 inches

Cable Opening Width:

0.240 inches

Operating Tempurature Rating:

Between -54.0 degrees celsius and 100.0 degrees celsius

Thready Qty Per Inch (tpi):

56

Thread Size:

0.086 inches

NSN 5935-00-983-5491 Electrical Plug Connector - Page 2 of 2



Back single matin	g end single contact grouping
Contact Material:	
Copper alloy singl	e mating end single contact grouping
Contact Surface	
Gold single mating	g end single contact grouping and nickel single mating end single contact grouping
Insert Material:	
Plastic diallyl phth	alate glass filled single mating end
Contact Surface	Treatment Specification:
Mil-g-45204, type	2, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal
specification 2nd t	reatment response single mating end single contact grouping
Terminal Type:	
Crimp single matir	ng end single contact grouping
Insert Material Sp	pecification:
Mil-p-19833, ty gd	i-30 military specification single material response single mating end
Included Contact	t Quantity:
14 single mating e	and single contact grouping
Included Contact	t Type:
Round pin single r	mating end single contact grouping
Precious Materia	I And Location:
Contact surfaces of	gold
Precious Materia	I And Weight:
0.081 gold grains,	troy
Precious Materia	l:
Gold	
Thread Series De	esignator:
Unc	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military S	Standard):
Mil-g-45204 spec.	