

View Online at <https://aerobasegroup.com/nsn/5935-00-983-6946>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Overall Length:

0.870 inches

Overall Height:

Between 0.510 inches and 0.610 inches

Overall Width:

0.340 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Size:

0.086 inches and 0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c or d, cl 1 military specification 1st treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, ty gdi-30 military specification single material response single mating end

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.