## NSN 5935-00-983-7287

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-983-7287 **Thread Class:** 2a **Thread Direction:** Right-hand **Environmental Protection:** Watertight **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 14 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded coupling nut Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.625 inches **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Insert Material Specification:** 

Mil-m-19833, ty gdi-30 military specification single material response single mating end

**Included Contact Quantity:** 

14 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-00-983-7287

Mil-std (military Standard):

Mil-m-19833 spec.

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-12520 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-12520 government specification
Shelf Life:
N/a
Unit Of Measure:
<b></b>
Demilitarization:
No
Fiig:
A039h0