NSN 5935-00-983-8873



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-983-8873 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Height:** 1.764 inches **Overall Width:** 1.498 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.625 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.281 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 28 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end all contact groupings **Polarization Method:** Mating end Shell Type: Solid **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:**

Silver single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end all contact groupings

NSN 5935-00-983-8873

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
3 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.028 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0