

View Online at <https://aerobasegroup.com/nsn/5935-00-984-3171>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Angle shape, external coupling

**Overall Length:**

0.695 inches

**Bushing Diameter:**

0.210 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.360 inches

**Overall Height:**

0.791 inches

**Overall Width:**

0.500 inches

**Environmental Protection:**

Vibration resistant and shock resistant and corrosion resistant and moisture resistant

**Unthreaded Mounting Hole Diameter:**

0.090 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.360 inches

**Flange Length:**

0.500 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.312 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic fluorocarbon single mating end and rubber silicone class q single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 1, grade c military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold and copper

**Shell Surface Treatment Specification:**

Mil-g-45204, type 1, grade c military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

**Shell Material Specification:**

Qq-c-530 federal specification single material response

**Insert Material Specification:**

Mil-p-19468 military specification 1st material response single mating end and zz-r-765, class 11 b, grade 50-60 federal specification 2nd material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Shell and contact surfaces gold

**Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-std-15004