Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-984-4357

## **Overall Length:**

Between 1.078 inches and 1.140 inches

### **Overall Height:**

1.438 inches

## **Overall Width:**

1.438 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

0.120 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 1.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

#### 1.187 inches

**Distance From Mounting Shoulder To Front Face:** 

## 0.531 inches

Mating End Quantity:

1

## **Contact Position Arrangement Style:**

37p single mating end

### Contact Removability:

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

0.0

#### Shell Type:

Solid

# **Connector Locking Method:**

Ball

# Terminal Location:

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

# Insert Material:

Plastic silicone single mating end

# **Terminal Type:**

Crimp single mating end single contact grouping



**Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 37 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.037 gold grains, troy and 0.037 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0