

NSN 5935-00-985-0364 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-985-0364 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 0.974 inches and 0.994 inches **Overall Height:** Between 3.927 inches and 3.947 inches **Overall Width:** Between 3.365 inches and 3.385 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.995 inches and 1.005 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.870 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 23 single mating end **Contact Removability:** Removable 2nd mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 10.0 2nd mating end 2nd contact grouping Shell Type: Solid **Connector Locking Method:**

Thready Qty Per Inch (tpi):

12

Thread Size:

0.312 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

NSN 5935-00-985-0364

Electrical Receptacle Connector - Page 2 of 2



insert Materiai:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
3 2nd mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.046 gold grains, troy and 0.046 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0